

Z形油封



代号	名称	截面图	材料	压力	温度	圆周速度	特点
ZF	Z形油封		橡胶	0	NBR -40至100 FKM -20至200	≤2	低速.密封脂

d	D	B1	B2	d	D	B1	B2	d	D	B1	B2	d	D	B1	B2
10	21	3	4.2	65	82	5	6.8	160	193	10	13.7	70	89	6	8.1
12	23	3	4.2	69.9	89	6	8.2	170	203	10	13.7	75	94	6	8.1
15	26	3	4.2	70	89	6	8.1	180	213	10	13.7	80	99	6	8.1
17	28	3	4.2	74.6	94	6	8.2	190	223	10	13.7	85	104	6	8.1
19.1	31	3	4.2	75	94	6	8.1	200	240	11	15.5	90	111	7	9.3
20	31	3	4.2	79.4	99	6	8.2	210	250	11	15.5	95	116	7	9.3
25	38	4	5.4	80	99	6	8.1	220	260	11	15.5	100	125	8	10.8
28.6	43	4	5.6	85	104	6	8.1	240	286	12	17.3	105	130	8	10.8
30	43	4	5.4	88.9	111	7	9.5	250	296	12	17.3	110	135	8	10.7
30.2	43	4	5.4	90	111	7	9.3	260	306	12	17.3	115	140	8	10.7
31.8	48	4	5.9	95	116	7	9.3	280	332	13	19	120	149	9	12.2
34.9	48	4	5.5	95.3	116	7	9.3	300	352	13	19.1	125	154	9	12.2
35	48	4	5.4	100	125	8	10.8	320	372	14	20	130	159	9	12.2
38.1	53	4	5.7	105	130	8	10.8	380	432	14	20	135	164	9	12.2
40	53	4	5.4	110	135	8	10.7	15	26	3	4.2	140	173	10	13.7
44.5	58	4	5.5	114	140	8	10.9	20	31	3	4.2	150	183	10	13.7
45	58	4	5.4	115	140	8	10.7	25	38	4	5.4	160	193	10	13.7
49.2	67	5	7.1	120	149	9	12.2	30	43	4	5.4	170	203	10	13.7
50	67	5	6.9	125	154	9	12.2	35	48	4	5.4	180	213	10	13.7
50.8	67	5	6.9	125	154	9	12.3	40	53	4	5.4	190	223	10	13.7
55	72	5	6.9	130	159	9	12.2	45	58	4	5.4	200	240	11	15.5
57.2	77	5	7.2	135	164	9	12.2	50	67	5	6.9	220	260	11	15.5
60	77	5	6.8	140	173	10	13.8	55	72	5	6.9	240	286	12	17.3
60.3	77	5	6.9	140	173	10	13.7	60	77	5	6.8				
63.5	82	5	7.1	150	183	10	13.7	65	82	5	6.8				